

# BL940-1100-01 High Power type Top LED with Lens

BL940-1100-01 is an GaAs LED mounted on copper heat sink and molded with epoxy lens.


On forward bias, it emits a band of radiation which peaks 940nm.

These devices are able to be operated at pulsed current of 4A under 2.6V for stable long life.

◆ Specifications

- 1) Product Name Super Flux type LED
- 2) Type No. BL940-1100-01
- 3) Chip
  - (1) Chip Material GaAs
  - (2) Chip Dimension 1000um\*1000um
  - (3) Peak Wavelength 940nm typ.
- 4) Package
  - (1) Type Super Beam type LED
  - (2) Resin Material Epoxy Resin
  - (3) Lead Frame Silver Plated Copper

◆ Outer dimension (Unit: mm)



◆ Absolute Maximum Ratings

| Item                  | Symbol           | Maximum Rated Value | Unit | Ambient Temperature  |
|-----------------------|------------------|---------------------|------|----------------------|
| Power Dissipation     | P <sub>D</sub>   | 900                 | mW   | T <sub>a</sub> =25°C |
| Forward Current       | I <sub>F</sub>   | 600                 | mA   | T <sub>a</sub> =25°C |
| Pulse Forward Current | I <sub>FP</sub>  | 4000                | mA   | T <sub>a</sub> =25°C |
| Reverse Voltage       | V <sub>R</sub>   | 10                  | V    | T <sub>a</sub> =25°C |
| Operating Temperature | T <sub>OPR</sub> | -30 ~ +85           | °C   |                      |
| Storage Temperature   | T <sub>STG</sub> | -30 ~ +100          | °C   |                      |
| Soldering Temperature | T <sub>SOL</sub> | 265                 | °C   |                      |

‡Pulse Forward Current condition: Duty=1% and Pulse Width=10us.

‡Soldering condition: Soldering condition must be completed within 3 seconds at 265°C

◆ Electro-Optical Characteristics [T<sub>a</sub>=25°C]

| Item                   | Symbol           | Condition             | Minimum | Typical | Maximum | Unit  |
|------------------------|------------------|-----------------------|---------|---------|---------|-------|
| Forward Voltage        | V <sub>F</sub>   | I <sub>F</sub> =200mA |         | 1.25    | 1.5     | V     |
| Pulsed Forward Voltage | V <sub>F</sub>   | I <sub>FP</sub> =4A   |         | 2.6     | 3.5     | V     |
| Reverse Current        | I <sub>R</sub>   | V <sub>R</sub> =10V   |         |         | 10      | uA    |
| Total Radiated Power   | P <sub>O</sub>   | I <sub>F</sub> =200mA | 25.0    | 45.0    |         | mW    |
| Radiant Intensity      | I <sub>E</sub>   | I <sub>F</sub> =200mA |         | 90      |         | mW/sr |
| Peak Wavelength        | λ <sub>P</sub>   | I <sub>F</sub> =50mA  |         | 940     |         | nm    |
| Half Width             | Δλ               | I <sub>F</sub> =50mA  |         | 60      |         | nm    |
| Viewing Half Angle     | θ <sub>1/2</sub> | I <sub>F</sub> =50mA  |         | ±7      |         | deg.  |
| Rise Time              | t <sub>r</sub>   | I <sub>F</sub> =50mA  |         | 1000    |         | ns    |
| Fall Time              | t <sub>f</sub>   | I <sub>F</sub> =50mA  |         | 500     |         | ns    |

‡Total Radiated Power is measured by Photodyne #500

‡Radiant Intensity is measured by Tektronix J-6512.