

# L1200-\_\_ \_\_

## Infrared LED Lamp

This series of L1200-\_\_ \_\_ is an InGaAsP LED mounted on a lead frame and encapsulated in various types of epoxy lens which offer different design settings.

On forward bias, it emits a high power radiation of typical 5.0mW with a peak wavelength at 1200nm.

### Specifications

- |                    |             |
|--------------------|-------------|
| 1. Chip material   | InGaAsP     |
| 2. Peak wavelength | 1200nm      |
| 3. Resin Material  | Epoxy resin |
| 4. Solder          | Lead free   |



### Absolute Maximum Ratings

Item	Symbol	Maximum Rated Value	Unit	Ambient Temperature
Power Dissipation	$P_D$	140	mW	$T_a=25^{\circ}\text{C}$
Forward Current	$I_F$	100	mA	$T_a=25^{\circ}\text{C}$
Pulse Forward Current	$I_{FP}$	1000	mA	$T_a=25^{\circ}\text{C}$
Reverse Voltage	$V_R$	5	V	$T_a=25^{\circ}\text{C}$
Operating Temperature	$T_{OPR}$	-30 ~ +85	$^{\circ}\text{C}$	
Storage Temperature	$T_{STG}$	-40 ~ +100	$^{\circ}\text{C}$	
Soldering Temperature	$T_{SOL}$	265	$^{\circ}\text{C}$	

### Electro-Optical Characteristics ( $T_a=25^{\circ}\text{C}$ )

Item	Symbol	Condition	Minimum	Typical	Maximum	Unit
Forward Voltage	$V_F$	$I_F=50\text{mA}$		1.1	1.5	V
Reverse Current	$I_R$	$V_R=5\text{V}$			10	$\mu\text{A}$
Radiated Power	$P_O$	$I_F=50\text{mA}$	3.0	5.0		mW
Peak Wavelength	$\lambda_P$	$I_F=50\text{mA}$	1150	1200	1250	nm
Half Width	$\Delta\lambda$	$I_F=50\text{mA}$		80		nm
Rise Time	$t_r$	$I_F=50\text{mA}$		10		ns
Fall Time	$t_f$	$I_F=50\text{mA}$		10		ns


**Characteristics of Radiant Intensity (Ta=25°C)**

Type	Viewing Half Angle	Radiant Intensity I <sub>F</sub> =50mA Unit : mW/sr			Outer Dimension	Dimension Figure
		Minimum	Typical	Maximum		
L1200-01					Φ5	1
L1200-02					Φ5	2
L1200-03	±10°		14		Φ5	3
L1200-04					Φ5	4
L1200-05					Φ5	5
L1200-06	±7°		38		Φ5	6
L1200-09					Φ5 Oval	7
L1200-46					Φ5	8
L1200-41					Φ4	9
L1200-42					Φ4	10
L1200-31					Φ3	11
L1200-33	±18°		9		Φ3	12
L1200-34					Φ3	13
L1200-36	±33°		4		Φ3	14

Radiant Power is measured by G8370-85

Brightness is measured by Tektronix J-16






**Outer Dimension of LED Lamp**





Outer Dimension of LED Lamp





<p><b>Figure-11 <math>\Phi 3</math>Mold (Type31)</b> cup position</p> <p>0.37 1max  <math>\phi 3.6 \pm 0.2</math>  <math>\phi 3 \pm 0.2</math>  <math>3.5 \pm 0.2</math> 21 min.          Cathode 1 typ.          Anode 1.5 typ.  <math>2-0.5sq \pm 0.1</math></p>	<p><b>Figure-12 <math>\Phi 3</math>Mold (Type33)</b> cup position</p> <p>2.65 1max  <math>\phi 3.8 \pm 0.2</math>  <math>\phi 3 \pm 0.2</math>  <math>5.3</math> 21 min.          Cathode 1 typ.          Anode 0.8 typ.  <math>2-0.5sq \pm 0.1</math></p>
<p><b>Figure-13 <math>\Phi 3</math>Mold (Type34)</b> cup position</p> <p>3.25 1max  <math>\phi 3.8 \pm 0.2</math>  <math>\phi 3 \pm 0.2</math>  <math>5.3 \pm 0.2</math> 21 min.          Cathode 1 typ.          Anode 1.5 typ.  <math>2-0.5sq \pm 0.1</math></p>	<p><b>Figure-14 <math>\Phi 3</math>Mold (Type36)</b> cup position</p> <p>2.1 1max  <math>\phi 4 \pm 0.2</math>  <math>\phi 3 \pm 0.2</math>  <math>5.3 \pm 0.2</math> 21 min.          Cathode 1 typ.          Anode <math>2 \pm 0.4</math>  <math>2-0.5sq \pm 0.1</math></p>
<p><b>Figure-15</b></p>	<p><b>Figure-16</b></p>
<p><b>Figure-17</b></p>	<p><b>Figure-18</b></p>
<p><b>Figure-19</b></p>	<p><b>Figure-20</b></p>





The Viewing half angle

<p><b>Figure-1 <math>\Phi 5</math>Mold (Type01)</b></p>	<p><b>Figure-2 <math>\Phi 5</math>Mold (Type02)</b></p> 
<p><b>Figure-3 <math>\Phi 5</math>Mold (Type03)</b></p> 	<p><b>Figure-4 <math>\Phi 5</math>Mold (Type04)</b></p> 
<p><b>Figure-5 <math>\Phi 5</math>Mold (Type05)</b></p> 	<p><b>Figure-6 <math>\Phi 5</math>Mold (Type06)</b></p> 
<p><b>Figure-7 <math>\Phi 5</math>Mold (Type09)</b></p>	<p><b>Figure-8 <math>\Phi 5</math>Mold (Type46)</b></p>
<p><b>Figure-9 <math>\Phi 4</math>Mold (Type41)</b></p>	<p><b>Figure-10 <math>\Phi 4</math>Mold (Type42)</b></p>


The Viewing half angle

<p>Figure-11 <math>\Phi</math>3Mold (Type31)</p>	<p>Figure-12 <math>\Phi</math>3Mold (Type33)</p> 
<p>Figure-13 <math>\Phi</math>3Mold (Type34)</p>	<p>Figure-14 <math>\Phi</math>3Mold (Type36)</p> 
<p>Figure-15</p>	<p>Figure-16</p>
<p>Figure-17</p>	<p>Figure-18</p>
<p>Figure-19</p>	<p>Figure-20</p>





**Recommended Land Layout (unit: mm)**



**Soldering Conditions**

