

L375-30M32L Higher beam type UVLED

L375-30M32L is an InGaN LED mounted on TO-18 stem and designed for narrow viewing angle +/-5° typ. with hermetical glass ball lens can. On forward bias it emits a spectral band of radiation, which peaks at 375nm.


◆Outer dimension (Unit: mm)

◆Features

- 1) Narrow viewing angle
- 2) High Radiant Intensity
- 3) High Reliability

◆Specifications

- 1) Product Name LED Lamp
- 2) Type No. L375-30M32L
- 3) Chip Spec.
 - (1) Material InGaN
 - (2) Peak Wavelength 375nm
- 4) Package
 - (1) Type TO-18 stem
 - (2) Lens Glass Ball Lens
 - (3) Cap Gold plated



◆Absolute Maximum Ratings

Item	Symbol	Maximum Rated Value	Unit	Ambient Temperature
Power Dissipation	PD	130	mW	Ta=25°C
Forward Current	IF	30	mA	Ta=25°C
Pulse Forward Current	IFP	50	mA	Ta=25°C
Reverse Voltage	VR	5	V	Ta=25°C
Operating Temperature	TOPR	-30 ~ +85	°C	
Storage Temperature	TSTG	-30 ~ +100	°C	
Soldering Temperature	TSOL	260	°C	

‡Pulse Forward Current condition: Duty=1% and Pulse Width=10us.

‡Soldering condition: Soldering condition must be completed within 3 seconds at 260°C

◆Electro-Optical Characteristics

Item	Symbol	Condition	Minimum	Typical	Maximum	Unit
Forward Voltage	VF	IF=20mA		3.6	4.0	V
Reverse Current	IR	VR=5V			10	uA
Total Radiated Power	PO	IF=20mA		0.6		mW
Radiant Intensity	IE	IF=50mA		18		mW/sr
Brightness	IV	IF=20mA		-		mcd
Peak Wavelength	λP	IF=20mA	370	375	380	nm
Half Width	$\Delta\lambda$	IF=20mA		10		nm
Viewing Half Angle	$\theta 1/2$	IF=20mA		± 5		°

‡Total Radiated Power is measured by Ando Optical Multi Meter AQ2140 & AQ2741.

‡Ando Optical Multi Meter AQ2140 is setted at 400nm range.

‡Radiant Intensity is measured by Epitex's designed and AQ2140 & AQ2741