

L565-__U Yellow Green LED Lamp

This series of L565-__U is a GaP LED mounted on a lead frame with a clear epoxy lens. On forward bias, it emits a band of visible light that peaks 565nm.

1) Specifications

- (1) Chip material GaP
- (2) Peak wavelength 565nm typ.
- (3) Package Clear epoxy resin
- (4) Lead frame Soldered

2) Absolute Maximum Ratings

Item	Symbol	Maximum Rated Value	Unit	Ambient Temperature
Power Dissipation	P _D	85	mW	T _a =25°C
Forward Current	I _F	30	mA	T _a =25°C
Reverse Voltage	V _R	5	V	T _a =25°C
Operating Temperature	T _{OPR}	-30 ~ +85	°C	T _a =25°C
Storage Temperature	T _{STG}	-30 ~ +100	°C	
Soldering Temperature	T _{SOL}	260	°C	

3) Electro-Optical Characteristics [T_a=25°C]

Item	Symbol	Condition	Minimum	Typical	Maximum	Unit
Forward Voltage	V _F	I _F =20mA		2.2	2.4	V
Reverse Current	I _R	V _R =5V			10	uA
Total Radiated Power	P _O	I _F =20mA		0.2		mW
Peak Wavelength	λ _P	I _F =20mA	555	565	575	nm
Half Width	Δλ	I _F =20mA		25		nm

4) Characteristics of Brightness [T_a=25°C]

Type	Viewing Half Angle	Brightness I _F =20mA unit: mcd			Outer Dimension	
		Minimum	Typical	Maximum	Dimension	Figure
L565-01U	±10°		600		Φ5	1
L565-02U	±5°				Φ5	2
L565-03U	±15°		400		Φ5	3
L565-04U	±20°		300		Φ5	4
L565-05U	±40°				Φ5	5
L565-06U	±6°		1000		Φ5	6
L565-09U	±25°(Long)		400		Φ5	7
	±15°(Short)				Oval	
L565-10U	±6°		1000		Φ10	8
L565-33U	±15°		200		Φ3	9
L565-36U	±30°		150		Φ3	10

‡ Brightness is measured by Tektronix J-16.

‡ Total Radiated Power is measured by Photodyne #500.