

L660N/850-04A Bi-Color LED for medical analysis

Bi-color LED of L660N/850-04A consists of AlGaInP and AlGaAs LEDs mounted on a lead frame with a clear epoxy lens.

On forward bias it emits a band of visible light, which peaks 660nm and 850nm at anode common.


◆ Features

- 1) High Reliability
- 2) High Power
- 3) Anode Common

◆ Specifications

- 1) Product Name Bi-color LED
- 2) Type No. L660N/850-04A
- 3) Chip
 - (1) Chip Material AlGaInP/AlGaAs
 - (2) Peak Wavelength 660nm / 850nm typ.
- 4) Package
 - (1) Type Φ 5mm clear molding
 - (2) Resin Material Epoxy Resin
 - (3) Lead Frame Soldered

◆ Outer dimension (Unit: mm)



◆ Absolute Maximum Ratings

Item	Symbol	Maximum Rated Value		Unit	Ambient Temperature
		660nm	850nm		
Power Dissipation	PD	120	160	mW	Ta=25°C
Forward Current	IF	50	50	mA	Ta=25°C
Reverse Voltage	IR	5		V	Ta=25°C
Operating Temperature	TOPR	-40 ~ +85		°C	
Storage Temperature	TSTG	-40 ~ +100		°C	
Soldering Temperature	TSOL	265		°C	

‡Soldering condition: Soldering condition must be completed within 3 seconds at 265°C

◆ Electro-Optical Characteristics [Ta=25°C]

Item	Symbol	Condition	Minimum		Typical		Maximum		Unit
			660nm	850nm	660nm	850nm	660nm	850nm	
Forward Voltage	VF	IF=20mA			2.1	1.4	2.3	1.6	V
Reverse Current	IR	VR=5V							uA
Total Radiated Power	PO	IF=20mA	8.0	4.8	15.0	7.0			mW
Peak Wavelength	λ_P	IF=20mA	650	830	660	850	670	870	nm
Half Width	$\Delta\lambda$	IF=20mA			18	35			nm
Viewing Half Angle	$\theta_{1/2}$	IF=20mA			±20				deg.

‡Total Radiated Power is measured by Photodyne #500

‡Radiant Intensity is measured by Tektronix J-6512