

L680-01AU


Infrared LED Lamp

L680-01AU is an AlGaAs LED mounted on a lead frame with a clear epoxy lens. On forward bias, it emits a spectral band of radiation that peaks at 680nm.

<Specifications>

1. Product Name: Infrared LED Lamp
2. Type Number: L680-01AU
3. Chip:
 - Chip material: AlGaAs
 - Peak Wavelength: 680nm typ.
4. Package
 - Type: Φ5mm Clear Molding
 - Resin Material: Epoxy Resin
 - Lead Frame: Soldered(Lead Free)

Outer Dimension (Unit:mm)



Absolute Maximum Ratings[Ta=25°C]			
Item	Symbol	Maximum Rated Value	Unit
Power Dissipation	PD	110	mW
Forward Current	IF	50	mA
Pulse Forward Current*	IFP	200	mA
Reverse Voltage	VR	5	V
Operating Temperature	TOPR	-30 ~ +85	°C
Storage Temperature	TSTG	-30 ~ +100	°C
Soldering Temperature**	TSOL	260	°C

* Duty=1% and Pulse Width=10us.

** Soldering condition must be completed within 3 second at 260 °C.

Electro-Optical Characteristics [Ta=25°C]						
Item	Symbol	Condition	Minimum	Typical	Maximum	Unit
Forward Voltage	VF	IF=20mA		1.9	2.3	V
Reverse Current	IR	VR=5V			10	uA
Total Radiated Power*	PO	IF=20mA	3	5		mW
Radiant Intensity**	IE	IF=20mA	15	30		mW/sr
Peak Wavelength	λP	IF=20mA	665	680	695	nm
Half Width	Δλ	IF=20mA		20		nm
Viewing half Angle	θ1/2	IF=20mA		±10		deg
Rise Time	tr	IF=20mA		80		ns
Fall Time	tf	IF=20mA		80		ns

* Measured by Photodyne #500

** Measured by Tektronix J-6512

