


L780/PD010-40D32-I

Metal Can Sealed PD Monitoring High Power LED

L780/PD010-40D32-I consists of a GaAlAs LED 780nm and a Si-PD mounted on TO-18 stem at anode common and hermetically sealed with a glass ball lens can. It is designed to monitor reflected light through detector for controlling its own output power.

Outer Dimension (Unit:mm)



<Specifications>

1. Product Name: LED Lamp with PD Monitor
2. Type Number: L780/PD010-40D32-I
3. Chip:
 - Chip Material: GaAlAs and Si(PIN)
 - Peak Wavelength: 780nm
4. Package
 - Stem: TO-18
 - Lens: $\Phi 5$ Glass Ball Lens
 - Can: Metal Can (Gold Plate)

Absolute Maximum Ratings [Ta=25°C]				
Device	Item	Symbol	Maximum Rated Value	Unit
LED	Power Dissipation	PD	200	mW
LED	Forward Current	IF	100	mA
LED	Pulse Forward Current*	IFP	500	mA
LED	Reverse Voltage	VR	5	V
PD	Reverse Voltage	VR	100	V
	Operating Temperature	TOPR	-30 ~ +85	°C
	Storage Temperature	TSTG	-30 ~ +100	°C
	Soldering Temperature**	TSOL	260	°C

* Duty=1% and tw=10us

** Soldering condition must be completed within 3 seconds at 260°C

Electro-Optical Characteristics [Ta=25°C]						
Item	Symbol	Condition	Minimum	Typical	Maximum	Unit
Forward Voltage	VF	IF=50mA		1.8	2.0	V
Reverse Current	IR	VR=5V			10	uA
Total Radiated Power*	PO	IF=50mA		12.0		mW
Radiant Intensity**	IE	IF=50mA		40.0		mW/sr
Peak Wavelength	λP	IF=50mA	760	780	800	nm
Half Width	$\Delta\lambda$	IF=50mA		35		nm
Viewing Half Angle	$\theta 1/2$	IF=50mA		± 15		deg
Rise Time	tr	IF=50mA		80		ns
Fall Time	tf	IF=50mA		80		ns
Output Current	IL	VR=0V		300		uA
Dark Current	ID	VR=10V			10	nA

* Measured by Photodyne #500

** Measured by Tektronix J-6512

