

SMT700


High Performance Infrared TOP IR LED

SMT700 consists of an AlGaAs LED mounted on the lead frame as TOP LED package and is sealed with epoxy resin.
It emits a spectral band of radiation at 700nm.

<Specifications>

1. Product Name: TOP IR LED
2. Type Number: SMT700
3. Chip:
 - Chip Material: AlGaAs
 - Peak Wavelength: 700nm
4. Package
 - Lead Frame Die: Silver Plated
 - Package Resin: PPA Resin
 - Lens: Epoxy Resin

Outer Dimension (Unit:mm)



Absolute Maximum Ratings				
Item	Symbol	Maximum Rated Value	Unit	Ambient Temperature
Power Dissipation	PD	100	mW	Ta=25°C
Forward Current	IF	50	mA	Ta=25°C
Pulse Forward Current*	IFP	200	mA	Ta=25°C
Reverse Voltage	VR	5	V	Ta=25°C
Operating Temperature	TOPR	-20 ~ +80	°C	
Storage Temperature	TSTG	-30 ~ +80	°C	
Soldering Temperature**	TSOL	240	°C	

* Duty=1% and Pulse Width=10us.

**Soldering condition must be completed within 3 second at 230 °C.

Electro-Optical Characteristics [Ta=25°C typ.]						
Item	Symbol	Condition	Minimum	Typical	Maximum	Unit
Forward Voltage	VF	IF=20mA		1.90	2.30	V
Reverse Current	IR	VR=5V			10	uA
Total Radiated Power*	PO	IF=20mA	1.5	3.0		mW
Radiant Intensity**	IE	IF=20mA	1.0	2.0		mW/sr
Peak Wavelength	λP	IF=20mA		700		nm
Half Width	$\Delta\lambda$	IF=20mA		20		nm
Viewing Half Angle	$\theta_{1/2}$	IF=20mA		± 55		deg
Rise Time	tr	IF=20mA		80		ns
Fall Time	tf	IF=20mA		80		ns

* Measured by Photodyne #500

** Measured by Tektronix J-6512

